HSLEDPB4, HSLEDPB5 & HSLEDPB6

PANAMA BATTEN FITTING

HiSPEC
LIFE SAFETY & HOUSING SOLUTIONS

PRODUCT FEATURES:

- **High lumen output –** Up to 10,500lm
- **High efficacy –** Up to 160lm/W
- **Long LED life –** > 54,000 hrs L70
- **3 CCT selectable –** 3000K / 4000K / 6500K
- **Plug & play modules -** Emergency Pack & Microwave Sensor compatible
- **Hinged lock-out gear tray –** Easy installation
- **Multiple conduit entry points –** Flexible wiring
- **Available in -** 4ft / 5ft / 6ft



DESCRIPTION:

The Panama batten range is a versatile, high-performance LED luminaire designed for a wide range of commercial and residential applications. Featuring a robust steel construction with an opal diffuser, it delivers high lumen output with excellent efficiency and long operational life. Engineered for flexibility and ease of installation, the Panama range incorporates plug and play Rio sensor technology, enabling energy efficient lighting control in most indoor environments.

PRODUCT CODES:

PRODUCT CODE	DESCRIPTION
HSLEDPB4	Panama Batten Fitting - 4ft
HSLEDPB5	Panama Batten Fitting - 5ft
HSLEDPB6	Panama Batten Fitting - 6ft

PLUG & PLAY MODULES:

PRODUCT CODE	DESCRIPTION
HSLEDRB-MOD/EP	Rio Batten Emergency Pack - Plug & Play
HSLEDRB-MOD/MS	Rio Batten Microwave Sensor Pack - Plug & Play

3 CCTK | 160 Lm/W | IP20 | FAST FIX | RoHS | CLASS1 | 5 YR GUARANTEE | 1 YR ON SITE WARRANTY | UK CA | CE | Member of theLIA

Includes fischer Duopower plugs & Fischer Screws

All information is subject to change and should be verified before any critical action.

Member of theLIA

PANAMA BATTEN FITTING

TECHNICAL SPECIFICATION:

PRODUCT CODE	HSLEDPB4	HSLEDPB5	HSLEDPB6
INPUT VOLTAGE	220-240v		
INPUT WATTAGE	4w adjustable - 19w, 24w, 28w, 34w	4w adjustable - 30w, 37w, 44w, 52w	4w adjustable - 36w, 45w, 53w, 62w
LUMEN OUTPUT	3100/3800/4600/5300lm	4800/6010/7100/8400lm	6100/7600/9000/10500lm
LUMENS PER WATT	160lm/w		
LED CHIPS	LED		
LED FORWARD VOLTAGE / CURRENT	83.2V-102.4V	101.4V-124.8V	156V-192V
LED CHIP LIFETIME *(L70)*	>54000 hours		
CCT SELECTABLE	3		
CCTK	3000K/4000K/6500K		
CRI/RA	Ra80		
SDCM	<6		
UGR	<22		
CLASS	I		
IP RATING	IP20		
IK RATING	IK06		
RATED LIFE	5 Years		
WARRANTY	5 Years		
AMBIENT OP. TEMP	-0°~ 45°C		
MICROWAVE SENSOR MODULE	Yes		
EMERGENCY PACK MODULE	Yes		

DIMENSIONS:



**All information is subject to change and should be verified before any critical action.*